

1 6. A stent according to claim 5 wherein the annular elastic core includes a nickel-
2 titanium alloy.

1 7. A stent according to claim 1 wherein the first terminal end includes a retention
2 ring, having an expanded ring state and a collapsed ring state, and being adapted to
3 spontaneously revert from the collapsed ring state to the expanded ring state to facilitate
4 retention of the retention ring within the bladder of the patient, and in the expanded ring
5 state, the retention ring extending axially from the wall of the stent.

1 8. A stent according to claim 1 wherein the second terminal includes a retention
2 ring, having an expanded ring state and a collapsed ring state, and being adapted to
3 spontaneously revert from the collapsed ring state to the expanded ring state to inhibit the
4 retention ring from passing through an external sphincter of the prostatic urethra of the
5 patient, and in the expanded ring state, the retention ring extending axially from the wall
6 of the stent.

1 9. A stent according to claim 1 wherein
2 the first terminal end includes a first retention ring, having a first expanded ring
3 state and a first collapsed ring state, in the first expanded ring state, the first retention ring
4 extending axially from the wall of the stent, and being adapted to spontaneously revert
5 from the first collapsed ring state to the first expanded ring state to facilitate retention of
6 the first retention ring within the bladder of the patient, and

7 the second terminal end includes a second retention ring, having a second
8 expanded second ring state and a second collapsed ring state, in the second expanded ring
9 state, the second retention ring extending axially from the wall of the stent, and being
10 adapted to spontaneously revert from the second collapsed ring state to the second
11 expanded ring state to inhibit the second retention ring from passing through the external
12 sphincter of the prostatic urethra of the patient.

1 10. A stent according to claim 1 wherein the wall further comprises at least one
2 through aperture extending between the inner surface and the outer surface for providing
3 fluid communication between the inner surface and the outer surface.

- 1 11. A stent according to claim 1 wherein the first outside cross-sectional diameter is
2 greater than the second outside cross-sectional diameter.
- 1 12. A stent according to claim 1 wherein the second outside cross-sectional diameter
2 is greater than the first outside cross-sectional diameter.
- 1 13. A stent according to claim 1, wherein the first terminal end comprises a domed
2 segment having inner and outer surfaces and extending axially from the wall of the stent
3 and adapted for facilitating insertion of the stent into the patient.
- 1 14. A stent according to claim 13 wherein the domed segment further comprises at
2 least one through aperture extending radially between the inner and outer surfaces of the
3 domed segment to provide fluid communication between the inner and outer surfaces of
4 the domed segment.
- 1 15. A stent according to claim 14 wherein the domed segment further comprises an
2 axially extending protuberance adapted for facilitating insertion of the stent into a patient.
- 1 16. A stent according to claim 15 wherein the axially extending protuberance has a
2 through aperture sized to accommodate a guide wire.
- 1 17. A stent according to claim 1 wherein the wall of the stent includes a radio-opaque
2 material.
- 1 18. A stent according to claim 1 wherein the wall comprises a coating.
- 1 19. A delivery system for deploying a self-expanding stent within a body lumen
2 comprising:
3 a retractable sheath comprising a wall and a proximal portion and a distal portion,
4 the retractable sheath defining an internal lumen extending from the proximal portion to
5 the distal portion, the internal lumen for containing the stent in a collapsed state at the
6 distal portion of the sheath, the wall defining a first groove and a longitudinal opening
7 through the proximal portion of the sheath, the first groove connected to and lying
8 perpendicular to a proximal end of the longitudinal opening;

9 a shaft partially disposed and slidably movable within the lumen of the sheath, the
10 shaft comprising at least one second groove; and

11 a rotatable locking element disposed over the proximal portion of the sheath, the
12 locking element comprising a tongue adapted to engage the first groove of the sheath and
13 the at least one second groove of the shaft, the stent being delivered by rotating the
14 locking element to position the tongue in the longitudinal opening of the sheath, and then
15 retracting the sheath over the shaft.

1 20. The delivery system of claim 19 further comprising a retraction handle disposed
2 on the proximal portion of the sheath, the retraction handle adapted to retract the sheath
3 over the shaft.

1 21. The delivery system of claim 19 further comprising an insertion handle disposed
2 on a distal end of the shaft, the insertion handle adapted to insert the delivery system into
3 a body of a patient.

1 22. The delivery system of claim 19 wherein the sheath comprises at least one
2 radiopaque locator band.

1 23. The delivery system of claim 19 wherein the shaft comprises a plurality of second
2 grooves.

1 24. The delivery system of claim 19 further comprising a slidable stop cup disposed
2 about the sheath to position the delivery system against a body of a patient before
3 deploying the stent.

1 25. The delivery system of claim 19 wherein the locking element further comprises a
2 thumb tab.

1 26. The delivery system of claim 19 wherein a distal end of the distal portion of the
2 sheath is rounded.

1 27. The delivery system of claim 19 wherein a distal end of the distal portion of the
2 sheath comprises a plurality of longitudinal slits.

allowing the liquid polymer to cure, and
removing the cured polymer for the injection mode, the cured polymer forming a
stent having,

a wall, disposed between the first and second terminal ends, and including an
inner surface and an outer surface, the inner surface defining a lumen extending between
the first and second ends, and the outer surface having a substantially smooth portion, the
wall having,

a first outside cross-sectional diameter at the first terminal end, a second
outside cross-sectional diameter at the second terminal end, and at least one intermediate
outside cross-sectional diameter at an intermediate location between the first and second
terminal ends, wherein at least one of the first and second outside cross-sectional
diameters is greater than the intermediate outside cross sectional diameter, and

an expanded state and a collapsed state, the wall being adapted to
spontaneously revert from the collapsed state to the expanded state.

35. A method of placing a collapsible and expandable stent within a body of a patient,
comprising:

providing a collapsible and expandable stent and a delivery system, the delivery
system comprising

a retractable sheath including a proximal portion and a distal portion, the
sheath defining an internal lumen extending from the proximal portion to the distal
portion, the internal lumen for containing the stent in a collapsed state at the distal portion
of the sheath, the wall defining a first groove and a longitudinal opening through the
proximal portion of the sheath, the first groove connected to and lying perpendicular to a
proximal end of the longitudinal opening;

a shaft partially disposed and slidably movable within the lumen of the
sheath, the shaft comprising at least one second groove; and

a rotatable locking element disposed over the proximal portion of the
sheath, the locking element comprising a tongue adapted to engage the sheath into the at
least one groove of the shaft;

inserting the delivery system with the stent collapsed within the sheath into the
body of the patient;

18 retracting the sheath over the shaft; and
 19 removing the delivery system from the body of the patient, thereby deploying the
 20 stent within the body.

1 36. The method of claim 35 wherein the delivery system further comprises a slidable
 2 stop cup disposed about the shaft and a thumb tab disposed on the locking element, and
 3 further comprising the step of locking the slidable stop cup against a head of a penis of
 4 the patient before insertion of the delivery system.

1 37. The method of claim 35 further comprising inserting the stent, in its collapsed
 2 state, into the sheath before the inserting step.